

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Product name : Tork Floral Air Freshener Spray
 Type of product : Aerosol
 Product group : Mixture of organic solvents, perfume and propellant

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : Professional use
 Use of the substance/mixture : Public domain (administration, education, entertainment, services, craftsmen). Air care products.
 Use of the substance/mixture : Fragranced metered aerosol space sprays designed for use in proprietary automated dispensers.
 Function or use category : Air freshener

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

SCA Hygiene Products AB
 Bäckstengatan, 5
 SE-40503 Göteborg - Sweden
 Contact person: Verena Ristau
 T +46 31 746 00 00
info@sca.com - <http://www.sca.com>

1.4. Emergency telephone number

Emergency number : 08-331231 (Sweden - Acute poisoning / Mon-Fri 9:00 -17:00)
 112 (24 hour service) – applicable to EU countries only

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol 1 H222;H229

Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC or 1999/45/EC

F+; R12

Full text of R-phrases: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

Signal word (CLP) : Danger
 Hazard statements (CLP) : H222 - Extremely flammable aerosol
 H229 - Pressurised container: May burst if heated
 Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
 P211 - Do not spray on an open flame or other ignition source
 P251 - Do not pierce or burn, even after use
 P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F

Tork Floral Air Freshener Spray

Safety Data Sheet

according to Regulation (EC) No. 453/2010

EUH phrases	: EUH208 - Contains 2,4-Dimethyl-3-cyclohexen-1-carboxaldehyde #(68039-49-6), Tetramethyl Acetyloctahydronaphthalenes #(54464-57-2). May produce an allergic reaction
Extra phrases	: Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C Do not pierce or burn, even after use Do not spray on a naked flame or any incandescent material

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Directive 67/548/EEC
Isobutane	(CAS No) 75-28-5 (EC no) 200-857-2 (EC index no) 601-004-00-0 (REACH-no) 01-2119485395-27	40 - 50	F+; R12
Ethanol #	(CAS No) 64-17-5 (EC no) 200-578-6 (EC index no) 603-002-00-5 (REACH-no) 01-2119457610-43	10 - 20	F; R11
Propane	(CAS No) 74-98-6 (EC no) 200-827-9 (EC index no) 601-003-00-5 (REACH-no) 01-2119486944-21	10 - 20	F+; R12
Isopropanol (Propan-2-ol) #	(CAS No) 67-63-0 (EC no) 200-661-7 (EC index no) 603-117-00-0 (REACH-no) 01-211947558-25	1 - 10	F; R11 Xi; R36 R67
4-Tertiary-butylcyclohexyl acetate #	(CAS No) 32210-23-4 (EC no) 250-954-9	< 1	N; R51/53
2,4-Dimethyl-3-cyclohexen-1-carboxaldehyde #	(CAS No) 68039-49-6 (EC no) 268-264-1	< 1	Xi; R36/38 Xi; R43 R52/53
Diphenyl Ether (Diphenyl ether (vapour)) #	(CAS No) 101-84-8 (EC no) 202-981-2	< 1	Xi; R36 N; R51/53
Tetramethyl Acetyloctahydronaphthalenes #	(CAS No) 54464-57-2 (EC no) 259-174-3 (REACH-no) 01-2119489989-04-XXXX	< 1	Xi; R38 Xi; R43 N; R51/53
2-Tertiary-butylcyclohexyl acetate #	(CAS No) 88-41-5 (EC no) 201-828-7	< 1	N; R51/53

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Isobutane	(CAS No) 75-28-5 (EC no) 200-857-2 (EC index no) 601-004-00-0 (REACH-no) 01-2119485395-27	40 - 50	Flam. Gas 1, H220 Press. Gas
Ethanol #	(CAS No) 64-17-5 (EC no) 200-578-6 (EC index no) 603-002-00-5 (REACH-no) 01-2119457610-43	10 - 20	Flam. Liq. 2, H225
Propane	(CAS No) 74-98-6 (EC no) 200-827-9 (EC index no) 601-003-00-5 (REACH-no) 01-2119486944-21	10 - 20	Flam. Gas 1, H220 Press. Gas
Isopropanol (Propan-2-ol) #	(CAS No) 67-63-0 (EC no) 200-661-7 (EC index no) 603-117-00-0 (REACH-no) 01-211947558-25	1 - 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
4-Tertiary-butylcyclohexyl acetate #	(CAS No) 32210-23-4 (EC no) 250-954-9	< 1	Aquatic Chronic 2, H411
2,4-Dimethyl-3-cyclohexen-1-carboxaldehyde #	(CAS No) 68039-49-6 (EC no) 268-264-1	< 1	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412
Diphenyl Ether (Diphenyl ether (vapour)) #	(CAS No) 101-84-8 (EC no) 202-981-2	< 1	Eye Irrit. 2, H319

Tork Floral Air Freshener Spray

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Tetramethyl Acetyloctahydronaphthalenes #	(CAS No) 54464-57-2 (EC no) 259-174-3 (REACH-no) 01-2119489989-04-XXXX	< 1	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
2-Tertiary-butylcyclohexyl acetate #	(CAS No) 88-41-5 (EC no) 201-828-7	< 1	Aquatic Chronic 2, H411

Full text of R- and H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove victim to fresh air.
First-aid measures after skin contact : Wash off immediately with soap and plenty of water.
First-aid measures after eye contact : Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes minimum).
First-aid measures after ingestion : IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : Dizziness, headaches, nausea.
Symptoms/injuries after skin contact : May cause skin irritation / dermatitis.
Symptoms/injuries after eye contact : May cause eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Carbon dioxide (CO2). Alcohol resistant foam.
Unsuitable extinguishing media : Do not use water jet.

5.2. Special hazards arising from the substance or mixture

- Hazardous decomposition products in case of fire : Carbon dioxide. carbon oxides.

5.3. Advice for firefighters

- Protective equipment for firefighters : Wear proper protective equipment.
Other information : Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Protective equipment : Use personal protective equipment as required. Evacuate personnel to a safe area.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

No special environmental precautions required.

6.3. Methods and material for containment and cleaning up

- For containment : Ensure adequate ventilation.
Methods for cleaning up : Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

6.4. Reference to other sections

Refer to sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Wear recommended personal protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ensure adequate ventilation of the storage area.

Tork Floral Air Freshener Spray

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Storage conditions	: Store tightly closed in a dry, cool and well-ventilated place. Keep away from sources of ignition - No smoking. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Receptacle under pressure. Storage at elevated temperatures may cause pressure build-up in sealed containers. Protect against direct sunlight. Store separately from oxidising agents and strongly alkaline and strongly acidic materials.
Storage temperature	: ≤ 50 °C

7.3. Specific end use(s)

Air care products.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Isobutane (75-28-5)		
Austria	MAK (mg/m ³)	1900 mg/m ³
Austria	MAK (ppm)	800 ppm
Finland	HTP-arvo (8h) (mg/m ³)	1900 mg/m ³
Finland	HTP-arvo (8h) (ppm)	800 ppm
Finland	HTP-arvo (15 min)	2400 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	1000 ppm
France	VME (mg/m ³)	1900 mg/m ³
France	VME (ppm)	800 ppm
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	2400 mg/m ³
Germany	TRGS 900 Occupational exposure limit value (ppm)	1000 ppm
Switzerland	VME (mg/m ³)	1900 mg/m ³
Switzerland	VME (ppm)	800 ppm
USA - ACGIH	ACGIH TWA (ppm)	1000 ppm
USA - NIOSH	NIOSH REL (TWA) (mg/m ³)	1900 mg/m ³
USA - NIOSH	NIOSH REL (TWA) (ppm)	800 ppm
Propane (74-98-6)		
Austria	MAK (mg/m ³)	1800 mg/m ³
Austria	MAK (ppm)	1000 ppm
Austria	MAK Short time value (mg/m ³)	3600 mg/m ³
Austria	MAK Short time value (ppm)	2000 ppm
Denmark	Grænseværdie (langvarig) (mg/m ³)	1800 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	1000 ppm
Denmark	Grænseværdie (kortvarig) (mg/m ³)	3600 mg/m ³
Denmark	Grænseværdie (kortvarig) (ppm)	2000 ppm
Finland	HTP-arvo (8h) (mg/m ³)	1500 mg/m ³
Finland	HTP-arvo (8h) (ppm)	800 ppm
Finland	HTP-arvo (15 min)	2000 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	1100 ppm
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	1800 mg/m ³
Germany	TRGS 900 Occupational exposure limit value (ppm)	1000 ppm
Poland	NDS (mg/m ³)	1800 mg/m ³
Norway	Gjennomsnittsverdier (AN) (mg/m ³)	900 mg/m ³
Norway	Gjennomsnittsverdier (AN) (ppm)	500 ppm
Switzerland	VME (mg/m ³)	1800 mg/m ³
Switzerland	VME (ppm)	1000 ppm
Switzerland	VLE (mg/m ³)	7200 mg/m ³
Switzerland	VLE (ppm)	4000 ppm
Canada (Quebec)	VEMP (mg/m ³)	1800 mg/m ³
Canada (Quebec)	VEMP (ppm)	1000 ppm
USA - ACGIH	ACGIH TWA (ppm)	1000 ppm
USA - NIOSH	NIOSH REL (TWA) (mg/m ³)	1800 mg/m ³
USA - NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	1800 mg/m ³

Tork Floral Air Freshener Spray

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Propane (74-98-6)		
USA - OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
Ethanol # (64-17-5)		
Austria	MAK (mg/m ³)	1900 mg/m ³
Austria	MAK (ppm)	1000 ppm
Austria	MAK Short time value (mg/m ³)	3800 mg/m ³
Austria	MAK Short time value (ppm)	2000 ppm
Belgium	Limit value (mg/m ³)	1907 mg/m ³
Belgium	Limit value (ppm)	1000 ppm
Bulgaria	OEL TWA (mg/m ³)	1000 mg/m ³
Czech Republic	Expoziční limity (PEL) (mg/m ³)	1000 mg/m ³
Czech Republic	Expoziční limity (PEL) (ppm)	530 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m ³)	3000 mg/m ³
Czech Republic	Expoziční limity (NPK-P) (ppm)	1590 ppm
Denmark	Grænseværdie (langvarig) (mg/m ³)	1900 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	1000 ppm
Denmark	Grænseværdie (kortvarig) (mg/m ³)	3800 mg/m ³
Denmark	Grænseværdie (kortvarig) (ppm)	2000 ppm
Estonia	OEL TWA (mg/m ³)	1000 mg/m ³
Estonia	OEL TWA (ppm)	500 ppm
Estonia	OEL STEL (mg/m ³)	1900 mg/m ³
Estonia	OEL STEL (ppm)	1000 ppm
Finland	HTP-arvo (8h) (mg/m ³)	1900 mg/m ³
Finland	HTP-arvo (8h) (ppm)	1000 ppm
Finland	HTP-arvo (15 min)	2500 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	1300 ppm
France	VME (mg/m ³)	1900 mg/m ³
France	VME (ppm)	1000 ppm
France	VLE (mg/m ³)	9500 mg/m ³
France	VLE (ppm)	5000 ppm
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	960 mg/m ³
Germany	TRGS 900 Occupational exposure limit value (ppm)	500 ppm
Greece	OEL TWA (mg/m ³)	1900 mg/m ³
Greece	OEL TWA (ppm)	1000 ppm
Hungary	AK-érték	1900 mg/m ³
Hungary	CK-érték	7600 mg/m ³
Ireland	OEL (8 hours ref) (mg/m ³)	1900 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	1000 ppm
Ireland	OEL (15 min ref) (ppm)	1000 ppm
Latvia	OEL TWA (mg/m ³)	1000 mg/m ³
Lithuania	IPRV (mg/m ³)	1000 mg/m ³
Lithuania	IPRV (ppm)	500 ppm
Lithuania	TPRV (mg/m ³)	1900 mg/m ³
Lithuania	TPRV (ppm)	1000 ppm
Lithuania	NRV (mg/m ³)	1900 mg/m ³
Lithuania	NRV (ppm)	1000 ppm
Netherlands	MAC TGG 8H (mg/m ³)	260 mg/m ³
Netherlands	MAC TGG 15MIN (mg/m ³)	1900 mg/m ³
Poland	NDS (mg/m ³)	1900 mg/m ³
Portugal	OEL TWA (ppm)	1000 ppm
Romania	OEL TWA (mg/m ³)	1900 mg/m ³
Romania	OEL TWA (ppm)	1000 ppm

Tork Floral Air Freshener Spray

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Ethanol # (64-17-5)		
Romania	OEL STEL (mg/m ³)	9500 mg/m ³
Romania	OEL STEL (ppm)	5000 ppm
Slovakia	NPHV (priemerná) (mg/m ³)	960 mg/m ³
Slovakia	NPHV (priemerná) (ppm)	500 ppm
Slovakia	NPHV (Hraničná) (mg/m ³)	1920 mg/m ³
Slovakia	Upozornenie (SK)	krátkodobý kategória II.
Slovenia	OEL TWA (mg/m ³)	1900 mg/m ³
Slovenia	OEL TWA (ppm)	1000 ppm
Slovenia	OEL STEL (mg/m ³)	7600 mg/m ³
Slovenia	OEL STEL (ppm)	4000 ppm
Spain	VLA-ED (mg/m ³)	1910 mg/m ³
Spain	VLA-ED (ppm)	1000 ppm
Spain	VLA-EC (mg/m ³)	1910 mg/m ³
Spain	VLA-EC (ppm)	1000 ppm
Sweden	nivågränsvärde (NVG) (mg/m ³)	1000 mg/m ³
Sweden	nivågränsvärde (NVG) (ppm)	500 ppm
Sweden	kortidsvärde (KTV) (mg/m ³)	1900 mg/m ³
Sweden	kortidsvärde (KTV) (ppm)	1000 ppm
United Kingdom	WEL TWA (mg/m ³)	1920 mg/m ³
United Kingdom	WEL TWA (ppm)	1000 ppm
United Kingdom	WEL STEL (mg/m ³)	5760 mg/m ³ (calculated)
United Kingdom	WEL STEL (ppm)	3000 ppm (calculated)
Norway	Gjennomsnittsverdier (AN) (mg/m ³)	950 mg/m ³
Norway	Gjennomsnittsverdier (AN) (ppm)	500 ppm
Norway	Gjennomsnittsverdier (Korttidsverdi) (mg/m ³)	1187,5 mg/m ³
Norway	Gjennomsnittsverdier (Korttidsverdi) (ppm)	625 ppm
Switzerland	VME (mg/m ³)	960 mg/m ³
Switzerland	VME (ppm)	500 ppm
Switzerland	VLE (mg/m ³)	1920 mg/m ³
Switzerland	VLE (ppm)	1000 ppm
Australia	TWA (mg/m ³)	1920 mg/m ³
Australia	TWA (ppm)	1000 ppm
Canada (Quebec)	VEMP (mg/m ³)	1880 mg/m ³
Canada (Quebec)	VEMP (ppm)	1000 ppm
USA - ACGIH	ACGIH TWA (mg/m ³)	1884 mg/m ³
USA - ACGIH	ACGIH TWA (ppm)	1000 ppm
USA - ACGIH	ACGIH STEL (ppm)	1000 ppm
USA - IDLH	US IDLH (ppm)	3300 ppm (10% LEL)
USA - NIOSH	NIOSH REL (TWA) (mg/m ³)	1900 mg/m ³
USA - NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	1900 mg/m ³
USA - OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
Isopropanol (Propan-2-ol) # (67-63-0)		
Austria	MAK (mg/m ³)	500 mg/m ³
Austria	MAK (ppm)	200 ppm
Austria	MAK Short time value (mg/m ³)	2000 mg/m ³ max. 4x15 min./Schicht
Austria	MAK Short time value (ppm)	800 ppm max. 4x15 min./Schicht
Belgium	Limit value (mg/m ³)	997 mg/m ³
Belgium	Limit value (ppm)	400 ppm
Belgium	Short time value (mg/m ³)	1248 mg/m ³
Belgium	Short time value (ppm)	500 ppm
Bulgaria	OEL TWA (mg/m ³)	980 mg/m ³
Bulgaria	OEL STEL (mg/m ³)	1225 mg/m ³

Tork Floral Air Freshener Spray

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Isopropanol (Propan-2-ol) # (67-63-0)		
Cyprus	OEL TWA (mg/m ³)	980 mg/m ³
Cyprus	OEL TWA (ppm)	400 ppm
Czech Republic	Expoziční limity (PEL) (mg/m ³)	500 mg/m ³
Czech Republic	Expoziční limity (PEL) (ppm)	203,5 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m ³)	1000 mg/m ³
Czech Republic	Expoziční limity (NPK-P) (ppm)	407 ppm
Czech Republic	Remark (CZ)	D
Denmark	Grænseværdie (langvarig) (mg/m ³)	490 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	200 ppm
Denmark	Grænseværdie (kortvarig) (mg/m ³)	980 mg/m ³
Denmark	Grænseværdie (kortvarig) (ppm)	400 ppm
Estonia	OEL TWA (mg/m ³)	350 mg/m ³
Estonia	OEL TWA (ppm)	150 ppm
Estonia	OEL STEL (mg/m ³)	600 mg/m ³
Estonia	OEL STEL (ppm)	250 ppm
Finland	HTP-arvo (8h) (mg/m ³)	500 mg/m ³
Finland	HTP-arvo (8h) (ppm)	200 ppm
Finland	HTP-arvo (15 min)	620 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	250 ppm
France	VLE (mg/m ³)	980 mg/m ³
France	VLE (ppm)	400 ppm
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	500 mg/m ³
Germany	TRGS 900 Occupational exposure limit value (ppm)	200 ppm
Germany	TRGS 903 (BGW)	50 mg/l Aceton (Blut; Expositionsende bzw. Schichtende)
Greece	OEL TWA (mg/m ³)	980 mg/m ³
Greece	OEL TWA (ppm)	400 ppm
Greece	OEL STEL (mg/m ³)	1225 mg/m ³
Greece	OEL STEL (ppm)	500 ppm
Hungary	AK-érték	500 mg/m ³
Hungary	CK-érték	2000 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	200 ppm
Ireland	OEL (15 min ref) (ppm)	400 ppm
Ireland	Notes (IE)	Sk
Latvia	OEL TWA (mg/m ³)	350 mg/m ³
Lithuania	IPRV (mg/m ³)	350 mg/m ³
Lithuania	IPRV (ppm)	150 ppm
Lithuania	TPRV (mg/m ³)	600 mg/m ³
Lithuania	TPRV (ppm)	250 ppm
Netherlands	MAC TGG 8H (mg/m ³)	650 mg/m ³
Netherlands	MAC TGG 8H (ppm)	250 ppm
Poland	NDS (mg/m ³)	900 mg/m ³
Poland	NDSCh (mg/m ³)	1200 mg/m ³
Romania	OEL TWA (mg/m ³)	200 mg/m ³
Romania	OEL TWA (ppm)	81 ppm
Romania	OEL STEL (mg/m ³)	500 mg/m ³
Romania	OEL STEL (ppm)	203 ppm
Slovakia	NPHV (priemerná) (mg/m ³)	500 mg/m ³
Slovakia	NPHV (priemerná) (ppm)	200 ppm
Slovakia	Upozornenie (SK)	krátkodobý kategória II.
Slovenia	OEL TWA (mg/m ³)	500 mg/m ³

Tork Floral Air Freshener Spray

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Isopropanol (Propan-2-ol) # (67-63-0)		
Slovenia	OEL TWA (ppm)	200 ppm
Spain	VLA-ED (mg/m ³)	998 mg/m ³
Spain	VLA-ED (ppm)	400 ppm
Spain	VLA-EC (mg/m ³)	1250 mg/m ³
Spain	VLA-EC (ppm)	500 ppm
Sweden	nivågränsvärde (NVG) (mg/m ³)	350 mg/m ³
Sweden	nivågränsvärde (NVG) (ppm)	150 ppm
Sweden	kortidsvärde (KTV) (mg/m ³)	600 mg/m ³
Sweden	kortidsvärde (KTV) (ppm)	250 ppm
United Kingdom	WEL TWA (mg/m ³)	999 mg/m ³
United Kingdom	WEL TWA (ppm)	400 ppm
United Kingdom	WEL STEL (mg/m ³)	1250 mg/m ³
United Kingdom	WEL STEL (ppm)	500 ppm
Norway	Gjennomsnittsverdier (AN) (mg/m ³)	245 mg/m ³
Norway	Gjennomsnittsverdier (AN) (ppm)	100 ppm
Switzerland	VME (mg/m ³)	500 mg/m ³
Switzerland	VME (ppm)	200 ppm
Switzerland	VLE (mg/m ³)	1000 mg/m ³ max. 4x15 min./Schicht
Switzerland	VLE (ppm)	400 ppm max. 4x15 min./Schicht
Australia	TWA (mg/m ³)	999 mg/m ³
Australia	TWA (ppm)	400 ppm
Australia	STEL (mg/m ³)	1250 mg/m ³
Australia	STEL (ppm)	500 ppm
Canada (Quebec)	VECD (mg/m ³)	1230 mg/m ³
Canada (Quebec)	VECD (ppm)	500 ppm
Canada (Quebec)	VEMP (mg/m ³)	983 mg/m ³
Canada (Quebec)	VEMP (ppm)	400 ppm
USA - ACGIH	ACGIH TWA (mg/m ³)	490 mg/m ³
USA - ACGIH	ACGIH TWA (ppm)	200 ppm
USA - ACGIH	ACGIH STEL (mg/m ³)	960 mg/m ³
USA - ACGIH	ACGIH STEL (ppm)	400 ppm
USA - NIOSH	NIOSH REL (TWA) (mg/m ³)	980 mg/m ³
USA - NIOSH	NIOSH REL (TWA) (ppm)	400 ppm
USA - NIOSH	NIOSH REL (STEL) (mg/m ³)	1225 mg/m ³
USA - NIOSH	NIOSH REL (STEL) (ppm)	500 ppm
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	980 mg/m ³
USA - OSHA	OSHA PEL (TWA) (ppm)	400 ppm
Diphenyl Ether (Diphenyl ether (vapour)) # (101-84-8)		
Austria	Local name	DIPHENYLETHER (DAMPF)
Austria	MAK (mg/m ³)	7 mg/m ³
Austria	MAK (ppm)	1 ppm
Belgium	Local name	Difenyloxyde (damp) / Oxyde de diphenyle (vapeur)
Belgium	Limit value (mg/m ³)	7 mg/m ³
Belgium	Limit value (ppm)	1 ppm
Belgium	Short time value (mg/m ³)	14 mg/m ³
Belgium	Short time value (ppm)	2 ppm
Bulgaria	Local name	ДифенилETER (ДифенилоКСИД)
Bulgaria	OEL TWA (mg/m ³)	5 mg/m ³
Croatia	Local name	Difenil-eter
Croatia	GVI (granična vrijednost izloženosti) (mg/m ³)	7,1 mg/m ³
Croatia	GVI (granična vrijednost izloženosti) (ppm)	1 ppm
Croatia	Naznake (HR)	Annex: I (Maximum Allowable Exposure Values)
Czech Republic	Local name	Difenyloxyde
Czech Republic	Expoziční limity (PEL) (mg/m ³)	5 mg/m ³

Tork Floral Air Freshener Spray

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Diphenyl Ether (Diphenyl ether (vapour)) # (101-84-8)		
Czech Republic	Expoziční limity (NPK-P) (mg/m ³)	10 mg/m ³
Denmark	Local name	diphenylether-
Denmark	Grænseværdie (langvarig) (mg/m ³)	7 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	1 ppm
Estonia	Local name	Difenüüleeter
Estonia	OEL TWA (mg/m ³)	7 mg/m ³
Estonia	OEL TWA (ppm)	1 ppm
Finland	Local name	FENYYLIEETTERI
Finland	HTP-arvo (8h) (mg/m ³)	7 mg/m ³
Finland	HTP-arvo (8h) (ppm)	1 ppm
Finland	HTP-arvo (15 min)	21 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	3 ppm
Finland	Huomautus (FI)	Source of Exposure Limits: Liite1
France	Local name	OXYDE DE BIPHÉNYLE
France	VME (mg/m ³)	7 mg/m ³
France	VME (ppm)	1 ppm
France	Note (FR)	OEL type: Indicative
Germany	Local name	Diphenylether
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	7,1 mg/m ³
Germany	TRGS 900 Occupational exposure limit value (ppm)	1 ppm
Germany	Remark (TRGS 900)	Peak Limitation Category: 1 - Peak Limitation Excursion Factor: 1 - Pregnancy Risk Group: C / Note(s): dfg100, dfg101
Greece	Local name	Διφαινυλαιθέρας (ατμοί)
Greece	OEL TWA (mg/m ³)	7 mg/m ³
Greece	OEL TWA (ppm)	1 ppm
Ireland	Local name	DIPHENYL ETHER (VAPOUR)
Ireland	OEL (8 hours ref) (mg/m ³)	7 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	1 ppm
Italy	Local name	Etere fenilico, vapori
Italy	OEL TWA (ppm)	1 ppm
Italy	OEL STEL (ppm)	2 ppm
Poland	Local name	Éter difenyłowy
Poland	NDS (mg/m ³)	7 mg/m ³
Poland	NDSCh (mg/m ³)	14 mg/m ³
Portugal	Local name	ÉTER FENÍLICO (VAPORES)
Portugal	OEL TWA (ppm)	1 ppm
Portugal	OEL STEL (ppm)	2 ppm
Romania	Local name	Fenileter (vapori)
Romania	OEL TWA (mg/m ³)	5 mg/m ³
Romania	OEL TWA (ppm)	0,7 ppm
Romania	OEL STEL (mg/m ³)	10 mg/m ³
Romania	OEL STEL (ppm)	1,4 ppm
Slovakia	Local name	difenyliéter
Slovakia	NPHV (priemerná) (mg/m ³)	7,1 mg/m ³
Slovakia	NPHV (priemerná) (ppm)	1 ppm
Slovakia	Upozornenie (SK)	Notes: T1
Slovenia	Local name	difenileter/bifenil - mešanica/para
Slovenia	OEL TWA (mg/m ³)	7,1 mg/m ³
Slovenia	OEL TWA (ppm)	1 ppm
Spain	Local name	FENILÉTER, VAPOR
Spain	VLA-ED (mg/m ³)	7,1 mg/m ³

Tork Floral Air Freshener Spray

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Diphenyl Ether (Diphenyl ether (vapour)) # (101-84-8)		
Spain	VLA-ED (ppm)	1 ppm
Spain	VLA-EC (mg/m ³)	14,2 mg/m ³
Spain	VLA-EC (ppm)	2 ppm
United Kingdom	Local name	DIPHENYL ETHER (VAPOUR)
United Kingdom	WEL TWA (mg/m ³)	7,1 mg/m ³
United Kingdom	WEL TWA (ppm)	1 ppm
Iceland	Local name	DIPHENYL ETHER (DIPHENYL OXIDE, PHENYL ETHER)
Iceland	OEL (8 hours ref) (mg/m ³)	7 mg/m ³
Iceland	OEL (8 hours ref) (ppm)	1 ppm
Norway	Local name	DIFENYLETER
Norway	Gjennomsnittsverdier (AN) (mg/m ³)	7 mg/m ³
Norway	Gjennomsnittsverdier (AN) (ppm)	1 ppm
Norway	Merknader (NO)	Evaporation factor for calculating OAR (Occupational Air Requirements) is: 0
Switzerland	Local name	Diphenylether (Dampf) / Etere fenilico, vapori / Oxyde de diphenyle (vapeurs)
Switzerland	VME (mg/m ³)	7 mg/m ³
Switzerland	VME (ppm)	1 ppm
Switzerland	VLE (mg/m ³)	7 mg/m ³
Switzerland	VLE (ppm)	1 ppm
Switzerland	Remark (CH)	STEL Time Limit (Freq. x Duration in minutes/shift): 15 min / Fertility toxin category: 3 / Embryo toxin category: 3 / SUVA Codes (See notes for meanings): C
USA - ACGIH	Remark (ACGIH)	Source of the OELs is: A (ACGIH OELs)

8.2. Exposure controls

Appropriate engineering controls	: Ensure adequate ventilation.
Personal protective equipment	: Handle in accordance with good industrial hygiene and safety practices.
Hand protection	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
Eye protection	: Avoid contact with eyes.
Skin and body protection	: Not required for normal conditions of use.
Respiratory protection	: Not required for normal conditions of use.
Other information	: Wash hands before breaks and after work.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Colour	: No data available
odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: Not applicable
Flash point	: Not applicable
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 3,5 - 4,5 bar
Relative vapour density at 20 °C	: No data available
Relative density	: 0,619 - 0,645
Solubility	: No data available

Tork Floral Air Freshener Spray

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 1,8 - 19 vol %

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions.

10.2. Chemical stability

Stable under use and storage conditions as recommended in section 7.

10.3. Possibility of hazardous reactions

Oxidizing agents, strong.

10.4. Conditions to avoid

Avoid high temperature (> 50 °C), heat, open flames and ignition sources.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Ethanol # (64-17-5)	
LD50 oral rat	6200 - 17800 mg/kg
Isopropanol (Propan-2-ol) # (67-63-0)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 inhalation rat (mg/l)	> 20 ppm

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: May cause skin irritation. May cause an allergic skin reaction.
Other information	: No data available on the product (mixture).

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No data available on the product (mixture).

Ethanol # (64-17-5)	
LC50 fishes 1	11400 mg/l (96 hours)
ErC50 (algae)	5000 mg/l (72 hours)

Tork Floral Air Freshener Spray

Safety Data Sheet

according to Regulation (EC) No. 453/2010

12.2. Persistence and degradability

Tork Floral Air Freshener Spray	
Persistence and degradability	Product evaporates rapidly when in contact with the air.

12.3. Bioaccumulative potential

Tork Floral Air Freshener Spray	
Bioaccumulative potential	No bioaccumulation.

12.4. Mobility in soil

Tork Floral Air Freshener Spray	
Ecology - soil	Evaporates rapidly.

12.5. Results of PBT and vPvB assessment

Tork Floral Air Freshener Spray	
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII	
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	

12.6. Other adverse effects

Other adverse effects	: No data available.
	: Avoid release to the environment

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Dispose of in compliance with all local and national regulations.
Waste treatment methods	: Contact a licensed waste disposal company.
Waste disposal recommendations	: Dispose of contents/container to comply with applicable local, national and international regulations.
Additional information	: Empty containers should be taken for recycling, recovery or waste in accordance with local regulation. Do not re-use empty containers.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No.	: 1950
--------	--------

14.2. UN proper shipping name

Proper Shipping Name	: AEROSOLS, flammable
Transport document description	: UN 1950 AEROSOLS, flammable, 2.1, (D)

14.3. Transport hazard class(es)

Class (UN)	: 2
Classification code (UN)	: 5F
Hazard labels (UN)	: 2.1



14.4. Packing group

Not applicable

14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available.

14.6. Special precautions for user

14.6.1. Overland transport

Transport regulations (ADR)	: Goods are classified as "Limited Quantities" and are therefore exempt from ADR/IMDG regulations. Check local legislation for domestic transport.
Classification code (UN)	: 5F

Tork Floral Air Freshener Spray

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Orange plates



Special provision (ADR) : 190, 327, 344, 625
Transport category (ADR) : 2
Tunnel restriction code : D
Limited quantities (ADR) : 1L
Excepted quantities (ADR) : E0

14.6.2. Transport by sea

Transport regulations (IMDG) : Subject to the provisions
Limited quantities (IMDG) : SP277
EmS-No. (Fire) : F-D
EmS-No. (Spillage) : S-U

14.6.3. Air transport

Transport regulations (IATA) : Subject to the provisions
Instruction "cargo" (ICAO) : 203
Instruction "passenger" (ICAO) : 203
Instruction "passenger" - Limited quantities (ICAO) : Y203

14.6.4. Inland waterway transport

No additional information available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

No REACH Annex XVII restrictions

Contains no REACH candidate substance

Other information, restriction and prohibition regulations

: Compliance with following regulations:

Aerosol products are manufactured in compliance with Commission Directive 2008/47/EC and the Directive 75/324/EEC and following amendments are applicable.

Seveso Information

:

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of R-, H- and EUH-phrases:

Aerosol 1	Aerosol, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	flammable liquids Category 2
Press. Gas	Gases under pressure
Skin Irrit. 2	skin corrosion/irritation Category 2
Skin Sens. 1	Sensitisation — Skin, category 1
Skin Sens. 1B	Sensitisation — Skin, category 1B
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H222	Extremely flammable aerosol

Tork Floral Air Freshener Spray

Safety Data Sheet

according to Regulation (EC) No. 453/2010

H225	Highly flammable liquid and vapour
H229	Pressurised container: May burst if heated
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects
R11	Highly flammable
R12	Extremely flammable
R36	Irritating to eyes
R36/38	Irritating to eyes and skin
R38	Irritating to skin
R43	May cause sensitisation by skin contact
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R67	Vapours may cause drowsiness and dizziness
F	Highly flammable
F+	Extremely flammable
N	Dangerous for the environment
Xi	Irritant

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product